

LPIC-1 101-500 – Lesson 1

103.1 Work on the Command Line (CLI)



Terminology

- There are many different terms related to the CLI:
 - **Shell:** the command line interface that runs in a terminal to execute commands.
 - **Terminal:** Programs that emulate the behavior of an old school Unix terminal (e.g. VT100)
 - **Console:** Synonym to Terminal

Examples of Shells

- **bash**: the most popular shell in Linux, default for most systems.
- **bsh**: a simple shell upon which bash was based on
- **dash**: combines the speed of bsh with the functionality of bash
- **csh/tcsh**: inspired from C. Fundamentally different from bash
- **ksh**: merges elements of bsh and csh
- **zsh**: a feature-rich and powerful shell



Examples of Terminals

- GNOME Terminal
- Konsole (KDE)
- xterm
- Terminator
- TTYs (Ctrl-Alt-F2 ... F6)
- MobaXterm (Windows)
- PuTTY (Windows)
- TeraTerm (Windows)
- Windows Subsystem for Linux - WSL (Windows)

The Shell Prompt

- **user@hostname: src\$**

The "\$" sign implies non privileged user

- **root@hostname:~#**

The "#" sign implies privileged user (root)

- **echo \$PS1**

The \$PS1 variable (Prompt String 1) defines the shell form:

[\\u@\\h \\w]\\\$

explanation: \\u: username, \\h:hostname \\w:basename

- Additional information:

\$ man bash # Lookup PROMPTING



Basic Command Syntax

- <command> <command options> <arguments>

e.g.:

```
$ ls -la src
```

```
total 24
```

```
drwxrwsr-x  6 root  src  4096 2011-06-21 11:34 .
```

```
drwxr-xr-x 11 root  root  4096 2011-05-29 14:34 ..
```

```
drwxr-xr-x  4 root  root  4096 2011-05-29 14:34 fglrx-  
8.840
```

```
drwxr-xr-x 24 root  root  4096 2011-05-29 14:30 linux-  
headers-2.6.38-8
```

```
drwxr-xr-x  7 root  root  4096 2011-05-29 14:30 linux-  
headers-2.6.38-8-generic
```

```
drwxr-xr-x 11 root  root  4096 2011-06-21 11:34  
virtualbox-ose-4.0.4
```

Builtins and external commands

- Builtin commands are commands provided by the shell itself, e.g. export, alias, cd etc
- more info: man builtins
- External commands are distinct executable files, e.g. **ls**, **man**, **which**

more info: **man <command>**

- There are commands that are both external and builtin, like **echo** and **pwd**

In this case priority goes to builtins



Basic Commands

- **cd:** change directory
- **pwd:** print working directory
- **echo:** print text/variables in stdout
- **export:** export variables
- **man:** manual pages for commands
- **uname:** system information
- **exec:** Execute a file
- **type:** Show type of command
- **exit:** exit current session/shell
- **logout:** exit current session
- **time:** calculate execution time
- **history:** show command history
- **env:** show environment variables
- **set:** show/set variables
- **unset:** unset variables
- **which:** show path of external command

Absolute – Relative Paths

- Absolute paths always start with “/”, e.g.:

/home/user/bin

- Relative path start from the current directory, e.g.:

./bin points to **/home/user/bin** if you are in **/home/user** already

- The dot and slash “**./**” can be omitted, e.g.:

bin points to **/home/user/bin** if you are in **/home/user** already

- A double dot and slash “**../**” is interpreted as “Go back one directory” e.g.:

../user2/bin points to **/home/user2/bin** if you are in **/home/user**

- The tilde character “**~**” and the variable **\$HOME** point to the current user’s home directory (homedir), e.g.

if the user name is “**user**” then **~/bin** and **\$HOME/bin** point to **/home/user/bin**

Command Execution

- First priority goes to builtins.
- Next priority goes to every executable file in the **\$PATH**, e.g.:

```
$ echo $PATH  
/home/theo/bin:/usr/local/sbin:/usr/local/bin:/usr/sbin:/us  
r/bin: /sbin:/bin:/usr/games
```

- Directories in the left side are given higher priority than directories in the right, e.g.
/home/theo/bin/ls has priority over **/bin/ls**

- `$ ls -l /bin/bash`

```
-rwxr-xr-x 1 root root 954896 2011-04-01 00:20 /bin/bash  
The x character states that the file /bin/bash is an executable.
```

Command Execution

- For commands not included in the **\$PATH** you should explicitly define the absolute or relative path, e.g: **/usr/lib/gettext/hostname** or **./commands/testing**
- The **exec** command can execute other executables
- To execute a command in the current directory we use “**./**” e.g.: **./testing**
- For successive command execution we can use “**;**” e.g.: **<cmd1> ; <cmd2> ; <cmd3>**



Command Substitution

- We can expand the output of a command to be used as an argument to another command.
- There are two ways to do this:
`$(command)` or ``command``.
The former is recommended as it is safer when there are strange meta-characters in the command
- `$ echo $HISTFILE # show the file where the command history is saved`
- `$ ls -l $(echo $HISTFILE) # The echo $HISTFILE command is invoked first and its output is passed as an argument to the ls -l command.`

Command Completion

- Bash as well as other shells provide a “**command completion**” feature by invoking the “**Tab**” key
- A single **Tab** will auto-complete the following characters, provided they are unique:

\$ pass<Tab> → \$ passwd

- Two successive **Tabs** will display other possible commands, if the set already typed is not unique:

\$ pas<Tab><Tab> →
passwd paste



Command Completion

- The same logic applies to paths, e.g.:

```
$ cd /var/lo<Tab><Tab> →  
local/ lock/ log/
```

- \$ cd /var/loca<Tab> →
\$ cd /var/local/

Note: some systems (like Ubuntu) have extended this concept to options/parameters completion or even the file type expected by the command.

Command History

- The **history** command will return a list with the most recent commands
- **\$HISTSIZE**: this variable will display the size of the command history
(default: **1000** commands)
- **\$HISTFILE**: this variable will return the command history file
(default: `~/.bash_history`)



Command History Expansion

- **!!** Executes the most recent command
- **!n** Execute the nth command. We can use the **history** command to see the command numbers.
- **!-n** Execute the nth from the end of the command history.
- **!string** execute the most recent command starting with the characters “**string**”.
- **!?string** execute the most recent command containing the characters “**string**”.
- **^string1^string2** repeat last command, replacing “**string1**” with “**string2**”.
- **\$ fc** edits the most recent command history

Shell Shortcuts

- **Ctrl-p** Go a command back (also ‘Up Arrow’)
- **Ctrl-n** Next command (also ‘Down Arrow’)
- **Ctrl-b** A character backwards (also ‘Left Arrow’)
- **Ctrl-f** A character forward (also ‘Right Arrow’)
- **Ctrl-a** Go to the beginning of a line (also ‘Home’)
- **Ctrl-e** Go to the end of line (also ‘End’)
- **Ctrl-t** Transpose the character left of the cursor with the character under the cursor
- **Ctrl-l** Clear screen but leave the current line to the top of the screen

Note: The Bash shell has the same shortcuts as the Emacs editor

Shell Shortcuts

- **Meta-<** Go to the top of the command history
- **Meta->** Go to the bottom of the command history
- **Ctrl-d** Delete character right of the cursor
- **Ctrl-k** Delete (kill) the text to the end of line
- **Ctrl-y** Paste (yank) the deleted text
- **Meta-d** Delete (kill) the current word
- **Ctrl-rtext** search text backwards
- **Ctrl-s** search text forward
- **Ctrl-x Ctrl-e** invoke the default text editor

Note: the ‘Meta’ key is usually assigned to the ‘Alt’ key

Environment and Shell Variables

- **\$ PROXY=http://proxy.domain.int #**
set a Shell variable
- **\$ export PROXY #** export a variable
to child shells
(Environment Variable)
- **\$ export**
PROXY=http://proxy.domain.int #
combine the previous two commands
in one



The `echo` command

- ```
$ echo $PROXY # show the value of the PROXY variable
```

  
`http://proxy.domain.int`
- ```
$ echo "Proxy = $PROXY" # Double quotes expand variable
```


`Proxy = http://proxy.domain.int`
- ```
$ echo 'Proxy = $PROXY' # Single quotes show the exact
```

  
`string`  
`Proxy = $PROXY`



# Commands env, set and unset

- The **env** command will return the list of environment variables:  
`$ env | more # (press q to exit more)`
- The **set** command will return the list of shell variables:  
`$ set | less # (press q to exit less)`
- `$ unset PROXY # unset the variable $PROXY from the Shell and Environment`
- `$ set -o # status of shell options`
- `$ set -o/+o <option> # set/unset shell options`
- `$ set -o vi # use vi shortcuts instead of emacs in the bash shell`
- `$ set +o history # disable the command history`
- `$ set -o allexport # export all variable to the Environment`

# The `uname` command

The **uname** command will return some useful information about our system

- **\$ uname -a** # display all available info
- **\$ uname -r** # kernel release
- **\$ uname -n** # machine hostname
- **\$ uname -v** # kernel version and info
- **\$ uname -o** # os name
- **\$ uname -s** # kernel name
- **\$ uname -m** # system architecture



# The `which` and `type` commands

- `$ which set` # no external command named `set`
- `$ type set` # set is a builtin command  
set is a shell builtin
- `$ which echo` # path of echo external command  
`/usr/bin/echo`
- `$ type echo` # `echo` is builtin AND external  
echo is a shell builtin
- `$ type ls` # ls is in fact an alias  
ls is aliased to `ls -color=auto`
- `$ \ls` # run the unaliased version of `ls`



# Getting Help with commands

- Most command support the **-h** or **--help** options (or both) for basic help, e.g.:
- **\$ ls --help**
- **\$ gzip -h**
- The **man** will give us a more detailed description of the command, e.g.:

```
$ man bash
```

- Some command make use of the **info** command for an even more detailed description. **info** supports hyperlinks. Example:

```
$ info date
```

**”When all else fails, read the manual”**  
**~ Ancient UNIX proverb ~**



# Manpages Sections


| Section ID | Description                |
|------------|----------------------------|
| 1          | User Programs and Commands |
| 2          | Kernel System Calls        |
| 3          | Library Calls              |
| 4          | Devices Files in /dev      |
| 5          | File Formats               |
| 6          | Games                      |
| 7          | Various                    |
| 8          | System commands            |
| 9          | Kernel Routines            |

# Using the `man` command

- `$ man -wa passwd # show all man files related to passwd`
- `$ man passwd # displays the first of the 3 pages based on the priority: 1:8:2:3:4:5:6:7:9`
- `$ man 1 passwd # shows the man page related to passwd in section 1`
- `$ man 1ssl passwd # shows the man page related to passwd in subsection 1ssl`
- `$ man 5 passwd # shows the man page related to passwd in section 5`
- `$ man -a passwd # shows successively all man pages named passwd`
- `$ man -f passwd # (identical to whatis) shows a brief description of all pages named passwd`
- `$ man -k passwd # (identical to apropos) shows a brief description of all pages containing passwd`
- `$ man -K passwd # shows successively all man pages named containing passwd in their content`



# License



The work titled "LPIC-1 101-500 – Lesson 1" by  
Theodosios Andreou is distributed with the  
Creative Commons Attribution ShareAlike 4.0  
International License.

